


HOMOGENEOUS
COMPACT VINYL

Contract Plus

CERTIFICATION & CLASSIFICATION		STANDARDS	Contract Plus
Type of floor covering	ISO 10581		Homogeneous single layered vinyl flooring
Binder content	ISO 10581		Type II
CE certification	EN 14041		Yes
Classification	ISO 10874		Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS		STANDARDS	Contract Plus
PUR			Yes
Total thickness	ISO 24346		2.0 mm
Total weight/m²	ISO 23997		3150 g
Form of delivery	ISO 24341 Sheet (rolls)		Approx. 23 running metres x 200 cm Art. no. 21455_ _ _ 3 digit colour number
TECHNICAL PERFORMANCES		STANDARDS	Contract Plus
Dimensional stability	ISO 23999		≤ 0.40 %
Flexibility	ISO 24344, Method A		No cracking on 20 mm mandrel
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		Class Bfl s1 ≥ 8 kW/m ² Pass
Residual indentation	ISO 24343-1		Required value: ≤ 0.10 mm Best measured value: 0.04 mm
Castor chair test	ISO 4918		Suitable
Marine certificate	IMO Res. MSC. 307(88) IMO (2010 FTPC) Annex 1, Part 5 and 2		 0038/2018 MED 1750031/M1 SAS F170034/M1
Static electrical discharge	EN 1815		< 2 kV
Total VOC emissions	ISO 16000-6		≤ 10 µg/m ³ (after 28 days)
Underfloor heating			Suitable – max 27°C
Thermal resistance	EN 12667		Approx. 0.01 m ² K/W
Light fastness	EN ISO 105-B02		≥ level 6
Chemical resistance	ISO 26987		Good resistance
Bacteria resistance	ISO 846:Part C		Does not favour growth
Slip resistance	DIN 51130 EN 13893		R9 ≥ 0.3
Seam strength	EN 684		Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Colours			24

The above information is subject to modification for the benefit of further improvement (01/2018).